


Microplate Shaker TiMix 5 control



Description

The Microplate Shaker TiMix 5 control guarantees optimal mixing of small sample volumes in microplates, deepwell-plates or other plates in microplate format. The wide choice of different rack systems allows fastening between 8 and 48 microplates. The shaker also has a touch display and programmable control.

Basic Equipment

Basic device without shaking plate, **without rack system**
With touch display and programmable control

Loading Capacity

Standard rack system 0052 101	8 microplates
Rack system with pins 0052 096	8 microplates
Standard rack system 0052 101 + Additional tray 0052 102	16 microplates
RS high clamping pins 0052 104	24 microplates

RS metal clamping pins 0052 125 48 microplates

Options

[USB 2.0 interface](#)

[RS 232 interface](#)

[Control interface](#)

[Safety Package](#)

[Defined stop](#)

Details

Motion:	exact orbital motion
Shaking platform:	400 x 300 mm for 8 microplates
Max. load:	5 kg
Shaking speed:	100 - 1400 rpm, in steps of 5
Stroke:	3 mm (Special stroke on request)
Runtime:	programmable / continuous
Order No.:	6167 000
Accessory:	Standard Rack System TiMix 5 Additional tray TiMix 5 Rack System with clamping pins Rack System with high clamping pins Rack System with metal clamping pins Rack System Combifix KS Universal tray KS Incubator Hood TH 15

Technical specifications

Electrical supply:	230 V or 115 V, 50 / 60 H please indicate in case of order
Enclosure protection:	IP 21
Heat emission:	approx. 11 W
Ambient temperature:	5°C to 50°C
Relative humidity:	~ 85 %
Dimensions (w x d x h):	510 x 490 x 150 mm
Weight:	20 kg