

Multi-Flask Shaker VKS 75 B control



Description

The big heavy-duty shaker VKS 75 B control with touch display and programmable control has a horizontal shaking motion, a speed range of 30 - 200 rpm and a stroke of 50 mm. The VKS 75 B control is ideally suited for high loads up to 75 kg. **(floor installation only!)**

Basic Equipment

Basic device **without shaking plate, without rack system**
With touch display and programmable control

Loading Capacity

Erlenmeyer flasks 500 ml	32 pieces
Erlenmeyer flasks 2000 ml	12 pieces
Separating funnels 1000 ml	6 pieces

You will find further loading possibilities [here](#)

[Loading details](#) against shaking speed.

Options:

[Stroke 36 mm](#)
[Stroke 60 mm](#)
[Stroke 80 mm](#)

[USB 2.0 interface](#)
[RS 232 interface](#)
[Control interface](#)

[Safety Package](#)

Details

Motion: reciprocating (horizontal)
Shaking platform: 760 x 600 mm
Max. load: 75 kg
Shaking speed: 30 - 200 rpm, in steps of 5
Stroke: 50 mm (option: 36, 60 or 80 mm)
Timer: programmable / continuous
Order no.: 6112 000
Accessory: Shaking plate VKS (1-storey)
Rack System Combifix VKS A
Rack System Combifix VKS B
Rack System Combifix VKS C
Universal tray VKS 1-storey
Rack System VKS (2-storey)
Rack System VKS "Giant" (3-storey)

Technical specifications

Electrical supply: 100 - 240 V, 50 / 60 Hz please indicate in case of order
Enclosure protection: IP 21
Heat emission: max. 15 W
Ambient temperature: 5°C to 50°C
Relative humidity: ~ 85 %
Dimensions (w x d x h): 1050 x 835 x 250 mm
Weight: 110 kg